

778nm Bandpass Filter for Pulse Power

FEATURES

- High Isolation
- Low Insertion Loss
- High Reliability and Stability
- Various Bandwidth
- High Optical Power

APPLICATIONS

- Broadband Systems
- Optical Amplifying Systems
- Telecommunication Networks
- Research Labs
- Laser Systems



SPECIFICATIONS

Parameters	Unit	Value	
Center Wavelength	nm	778	
Min. Pass Band Width @ 0.5dB	nm	2.0	
Insertion Loss over Pass Band Wavelength	dB	≤1.6	
Stop Wavelength (ASE)	nm	700-774&782-850	
Stop Wavelength (ASE) Isolation	Standard High Isolation	dB dB	≥25 ≥45
ASE Direction	-	F: Forward, B: Backward, T: Two-way	
Configuration	-	D: 2-port, Y: 3-port, X: 4-port	
Optical Return Loss	dB	≥50	
Polarization Dependent Loss	dB	≤0.15	
Fiber Type	Input&Output ASE Guide Out (Y/X Type)	- -	HI780 Fiber or 780-HP Fiber(7) Same Fiber or MM Fiber
Fiber Tensile Load	N		5
Max. Average Optical Power (ASE+Signal)	W		0.3, 0.5, 1, 2, 3, 5, 10, 15, 20
Max. Peak Power for pulse	kW		0.1, 1, 2, 3, 5, 10, 15, 20
Max. ASE Average Power	W		0.3, 0.5, 1, 2, 3, 4, 5, 10
Operating Temperature	°C		0~50
Storage Temperature	°C		-40~85
Package Dimension	Stainless Steel Tube (SST) Metal Box	mm mm	∅5.5x ^L 38 (≤5W); ∅6.0x ^L 50 (5~10W) H: ^L 90x ^W 12x ^H 10 (>10W); M: ^L 120x ^W 12x ^H 10 (≤10W)

- Note:**
- Specifications are for device without connectors; Specifications may change without notice.
 - To add connectors, IL is 0.7dB higher, RL is 5dB lower.
 - Suggest to use Y/X type or H Box if blocked optical power is ≥1W.
 - Only guarantee 1W continuous wave (CW) power thru testing for connectors added.
 - Devices for higher optical power or with other type fiber or consigned fiber are also available; Devices can only work in the core of Double Cladding (DC) Fiber, Cladding Power must be stripped before connecting the device.
 - Package size may be different for different optical power and configurations.

ORDERING INFORMATION (PN)

FFBP-778-NN(C)(C) - (C) (C) -H NN PNN -(NN) -(C) (C) C NN -CC/CCC												
Bandwidth	ASE Type	ASE Iso	Fwd ASE Fiber	Dwd ASE Fiber	Average Power	Peak Power	ASE Power	Package	Fiber Type	Fiber Sleeve	Fiber Length	Connector Type
20~2nm	B=Backward T=Two-way	I=High Isolation	Y=Same Fiber A=105/125um Fiber	Y=Same Fiber A=105/125um Fiber	0.3~300mW 1~1W	01~100W 1~1kW	1~1W 5~5W	M=Metal Box H=H Box	7~780-HP Fiber Blank for HI780 Fiber	B= Bare fiber L= Loose Tube	05~0.5m 10~1.0m	N=Without Connector FC/APC=FC/APC Connector
	Blank for Forward	Blank for	N=None Blank for D Type	5=50/125um Fiber Blank for None or D Type	5~5W 20~20W	10~10kW 20~20kW	10~10W Blank for 300mW	Blank for SST		2=2mm Cable 3=3mm Cable	15~1.5m 20~2.0m	LC/PC=LC/PC Connector SC/UPC=SC/UPC Connector